

## Republic of the Philippines TARLAC STATE UNIVERSITY

## **BIDS AND AWARDS COMMITTEE**

Romulo Blvd., San Vicente, Tarlac City Tel. No.: (045) 982-4630 Website: www.tsu.edu.ph

July 4, 2023

## **BID BULLETIN NO. 1**

## Project: Supply and Delivery of Equipment for Composting, Rebid

This Bid Bulletin no. 1 is issued to clarify items and shall be an integral part of the Bidding Documents.

Please be informed of the modification in the bidding documents.

POSTED TO PHILGEPS		MODIFICATION	
Section VII. TECHNICAL SPECIFICATIONS		Section VII. TECHNICAL SPECIFICATIONS	
No. 1.	Description  Large Oscillating-Cylinder Rotary Screen/Shifter With Screw Conveyor, Main Frame: 1/4 stainless Perforated screen on 3/8 x 1 1/2 Circular Frame with 208 pillow blocks, Main Base: Standard angle bars, Engine: 3HP Electric Motor (Copper) single phase with push button switch, Steel Hopper; 3mm Standard checkered plate steel (inlet and outlet) Screw Conveyor (Main Casing: U-Shape 3mm stainless steel 304, Belt: 4mm MS plate-6 inch pitch maximum on 32mm diameter shafting with 32mm flange baring (Both end and twin 8mm thick flanges)), Base Frame: Standard angle bars with 4-12 inches donut tires, Engine: 3HP Electric Motor (Copper) Single phase with push button switch.	1. LSF	Description Descri
2.	Shredder, Portable Multipurpose Shredder: Trailer Type (Capacity: 80-120/hr, Main casing: 8mm standard MS Plate Steel, Steel Hopper: 3mm Standard checkered plate steel, main base: 2x4 C-Channel chasis with tool box, Main frame: 6mm x 50 mm Standard angle bars, Wheels 12" pneumatic tires (tubeless), Blade: Hightempered steel on claw steel base (Inside: 5/8 x 2 1/4 high carbon bolts on 3 inch, shafting with 32mm flange bearings), Engine: 12HP Kubota Diesel Motor), Inclusion upon purchase: 3 Shredder screen with 3 different holes sizes.	T C H S to C G ff K	Shredder, Portable Multipurpose Shredder: Trailer Type (Capacity: 80-120/hr, Main asing: 8mm standard MS Plate Steel, Steel dopper: 3mm Standard checkered plate steel, main base: 2x4 C-Channel chasis with colloox, Main frame: 6mm x 50 mm Standard angle bars, Wheels 12" pneumatic ires (tubeless), Blade: Hightempered steel on claw steel base (Inside: 5/8 x 2 1/4 high carbon bolts on 3 inch, shafting with 32mm lange bearings), Watercool Engine: 12HP (ubota Diesel Motor), Inclusion upon burchase: 3 Shredder screen with 3 different coles sizes

DR. MURPHY P. MOHAMMED
Chairperson